



MATERIAL:

- SV BODY: 416 SS
- HOUSING: CARBON STEEL
- HANDLE, DETENT & SPACERS: PLATED CARBON STEEL
- SHAFT: 416 SS
- SHEARFLO SEALING COMPONENTS: 440c HARDENED
- O-RINGS: BUNA (NITRILE)
- BACKUPS: TEFLON

MODEL NO: SV-25 2N5BPS1SN
 ROTOR: Selector
 ALL PORTS: 1/4" NPT
 WORKING PRESSURE: 5000 PSI
 Cv: .95
 Flow (GPM): 10
 TEMP RATING: -30° TO 180°F

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PacSeal Hydraulics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PacSeal Hydraulics IS PROHIBITED.

PacSeal Hydraulics Inc.

VALVES, ACCUMULATORS, CONTROLS

TITLE
 SV-25 Back Ported, 5K
 Spring Centered

SIZE A	DWG. NO. 40-1497	REV 2
SCALE: 1:2	WEIGHT: 5	SHEET 1 OF 1