



Model No. KR-175N5DFSH  
 MAX INLET: 5000 PSI  
 REGULATED OUTLET: 300-3000 PSI  
 SPECIFIED FLOW: 250 GPM  
 Cv Outlet: 27  
 Cv Vent: 4.1  
 VENT PORT: (2) 1" NPT  
 INLET PORTS (2): 1" NPT  
 OUTLET PORT: 2" NPT  
 OPERATOR: MANUAL OPERATOR

- MATERIALS:**
- BODY: STAINLESS STEEL
  - FLANGES & OPERATORS: CARBON STEEL
  - INTERNAL: STAINLESS STEEL
  - O-RINGS: BUNA (NITRILE)
  - BACKUPS: TEFLON
  - BOLTS : STEEL (A574)

TEMPERATURE RATING: -30°F TO 180°F  
 EST WEIGHT: 97 LBS

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PacSeal Hydraulics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PacSeal Hydraulics IS PROHIBITED.

	NAME	DATE
DRAWN	FS	3/1/17
CHECKED	LB	3/1/17
ENG APPR.	JB	3/1/17

COMMENTS:



**PacSeal Hydraulics**

TITLE:  
**KR-175 - Failsafe Hydraulic**

SIZE <b>A</b>	DWG. NO. <b>40-3316</b>	REV <b>3</b>
SCALE: 1:6	WEIGHT: 99	SHEET 1 OF 2

